


Weather Envoy

Wireless and Cabled Models



6316
6316C

Vantage Pro2™ Systems

The Wireless Weather Envoy (# 6316) and Cabled Weather Envoy (# 6316C) provide a quick and easy way to get weather data onto your Windows® or Macintosh® computer using WeatherLink® software.

Weather Envoy includes sensors to measure inside temperature, inside humidity, and barometric pressure. It is intended to be used in conjunction with our Integrated Sensor Suite (ISS) to report outside temperature and humidity, rainfall, wind speed and direction. Using optional sensors, the Weather Envoy can also report solar and UV radiation.

In the wireless version only, you may connect an external temperature probe (6475 or 6477) to replace the Weather Envoy's internal temperature sensor. The Wireless Weather Envoy can also be used in conjunction with our Wireless Temperature, Wireless Temperature and Humidity, and Wireless Leaf and Soil Moisture/Temperature stations. All wireless products communicate via FCC-certified, license-free transmitters and receivers.

The Cabled Weather Envoy is connected directly to the ISS via a cable and cannot be used with any other sensor stations and cannot be used with the Vantage Pro2 console.

Weather Envoy is powered by an included AC-power adapter with three AA battery backup. (Lithium batteries are recommended in low temperature applications.)

Please refer to the Wireless or Cabled Vantage Pro2, (and optional external temperature probe, if used) specification sheets for detailed information outdoor sensors.

General

Operating Temperature	0° to +140°F (-18° to +60°C)
Storage Temperature	-22° to +158°F (-30° to +70°C)
Current Draw, Wireless	0.90 mA average, 20 mA peak, (plus 0.125 mA for each optional wireless transmitter in use) at 4 to 6 VDC
Current Draw, Cabled	10 mA average, 15 mA peak at 4 to 6 VDC
AC Power Adapter.	5 VDC, 200 mA, regulated
Batteries	3 AA-cells
Backup Battery Life, Wireless	up to 4 months
Backup Battery Life, Cabled	up to 1 month
Connectors	Modular RJ-11
Cable Type (cabled only, not included)	4-conductor, 26 AWG
Housing Material	UV-resistant PVC plastic
Dimensions (length x width x height).	6.5" x 1.5" x 3.75" (165 mm x 38 mm x 95 mm)
Weight (with batteries).	0.58 lbs. (0.26 kg)

Communication (Wireless Version Only)

Transmit/Receive Frequency	US Models: 902-928 MHz FHSS, Overseas Models: 868.0 - 868.6 MHz FHSS.
ID Codes Available	8
Output Power	902-928 MHz FHSS: FCC-certified low power, less than 8 mW, no license required; 868.0 - 868.6 MHz FHSS. CE-certified, less than 8 mW, no license required
Range	
Line of Sight	up to 1000 feet (300 m)
Through Walls	200 to 400 feet (75 to 150 m)

Sensor Inputs

RF Filtering	RC low-pass filter on each signal line
------------------------	--

Weather Envoy**Sensor Data From Envoy**

Barometric Pressure (sensor located in Envoy)

Resolution and Units	Measured in 0.01" Hg. Other units are converted from Hg and rounded to nearest 0.1 mm, 0.1 hPa, 0.1mb.
Corrected Range	26.00" to 32.00" Hg, 660 to 810 mm Hg, 880 to 1080 hPa or mb
Uncorrected Range	16.00" to 32.50" Hg, 410 to 820 mm Hg, 540 to 1100 hPa or mb
Elevation Range	-1500' to +15,300' (-460 m to 4670 m)
Uncorrected Reading Accuracy	±0.03" Hg (±0.8 mm Hg, ±1.0 hPa/mb) (at room temperature)
Sea-Level Reduction Equation Used	United States Method employed prior to use of current "R Factor" method
Equation Source	Smithsonian Meteorological Tables
Equation Accuracy	±0.01" Hg (±0.3 mm Hg, ±0.3 hPa/mb)
Elevation Accuracy Required	±10' (3m) to meet equation accuracy specification
Overall Accuracy	±0.04" Hg (±1.0 mm Hg, ±1.4 hPa/mb)
Trend (change in 3 hours)	Change ±0.06" (2.0 hPa/mb, 1.5 mm Hg) = Rapidly Change ±0.02" (0.7hPa/mb, 0.5 mm Hg) = Slowly
Trend Indication	5 position arrow: Rising (rapidly or slowly), Steady, or Falling (rapidly or slowly)
Update Interval	1 minute
Current and Historical Data	Based on WeatherLink display
Alarms	High Threshold from Current Trend for Storm Clearing (Rising Trend) Low Threshold from Current Trend for Storm Warning (Falling Trend)
Range for Rising and Falling Trend Alarms	0.01 to 0.25" Hg (0.1 to 6.4 mm Hg, 0.1 to 8.5 hPa/mb)

Humidity

Inside Relative Humidity (sensor located in Weather Envoy)

Resolution and Units	1%
Range	1 to 100% RH
Accuracy	±3% from 1% to 90%; ±5% from 90% to 100%
Update Interval	1 minute
Current and Historical Data	Based on WeatherLink display
Alarms	High and Low Threshold from Instant Reading

Temperature

Inside Temperature (sensor located in Weather Envoy), or with optional external temperature probe

Resolution and Units	Current Data: 0.1°F or 1°F or 0.1°C or 1°C.°(nominal). Celsius is converted from Fahrenheit and rounded to the nearest 0.1° or 1°C. Historical Graph Data and Alarms: 1°F or 1°C. Celsius is converted from Fahrenheit and rounded to the nearest 1°C.
Range	
Inside	0° to +140°F (-18° to +60°C)
External Temperature Probe	-40° to +150°F (-40° to +65°C)
Sensor Accuracy	±1°F (±0.5°C) typical
Update Interval	1 minute
Current and Historical Data	Based on WeatherLink display
Alarms	High and Low Thresholds from Instant Reading

Clock

Resolution	1 minute
Units	Time: 12 or 24 hour format (user-selectable) Date: US or International format (user-selectable)
Accuracy	±8 seconds/month
Adjustments	
Time	Automatic Daylight Savings Time (for users in North America, Europe and Australia that observe it in AUTO mode, MANUAL setting available for all other areas)
Date	Automatic Leap Year

Package Dimensions

Product #	Package Dimensions (Length x Width x Height)	Package Weight	UPC Codes
6316	10.25" x 5.63" x 3.0" (260 mm x 143 mm x 76 mm)	1 lb. (0.45 kg)	011698 00749 3
6316EU			011698 00770 7
6316UK			011698 00771 4
6316C			011698 00757 8
6316CEU			011698 00789 9
6316CUK			011698 00790 5